

9090 Nieman Road • Overland Park, KS 66214 • (913) 888-7340 • Toll Free: 877-932-3645 • info@infinityfoils.com • infinityfoils.com

DuploFLEX FOL®

Product Data Sheet

Material Specifications	
Standard Width:	12.205" (310mm)
Standard Length:	14.7638' (4.5m)
Standard Thickness:	.004" (.102mm)
Product Description and Key	/ Features
	DuploFLEX FOL is a polyester-based, double-sided adhesive tape designed for mounting pre-cast counters. When applied to the back of a pre-cast counter, DuploFLEX FOL provides tremendous holding power which helps to assure the counter won't move or "walk" on press.
Detail:	Can be cut to size; very tacky; produced with a textured, green carrier sheet on one side
Product Performance	
Adhesion Characteristics*:	Good adhesion; heavier engraved designs may require additional mechanical fastening
Bonding Temperature:	Dependent upon the type and thickness of material being bonded; bonds at room temperature
Storage	
	Dry, climate-controlled conditions
Recommended For	
	Embossing, debossing and combination (fluted) jobs

*Disclaimer: Before using this product, you must evaluate it and determine if it is suitable for your application. Storage conditions, metal type, temperature, size/weight, and cleanliness will affect bonding.

© 2018 Infinity Foils, Inc.

This product data sheet remains the property of Infinity Foils, Inc. For duplications, in whole or part, authorization from Infinity foils, Inc. is required.