F

А

UEI

FOILS, INCORPORATED

GROUP

Y[®]

COMPANY

Section 1	Chemical Product and Cor	npany Identificat	ion	
Product Identifier	Epoxy Glass Board			
General Use	Counters for copper and brass stamping dies			
Company: Address:	Infinity Foils, Inc. – A UEI Group Company 9090 Nieman Road Overland Park, KS 66214			
Phone:	+1 913 888 7340 or +1 877 932 3645 (US Only)			
Emergency Contact Number	CHEMTEL – Available 24 hours/day, 7 days/week Domestic North America: +1 800 255 3924 International: +1 813 248 0585			
Section 2	Hazards Identification			
	During normal operation and usage, this solid material article does not present inhalation, ingestion, or chemical hazards. When this article is machined or otherwise modified by the user, chips containing filaments and fine or tacky dusts may be created in quantities substantial enough to affect the functionality of machines and equipment and may be potentially hazardous if the exposure limits described in Section 8 are exceeded. Hazardous Ingredients / Identity Information			
				h to affect the func-
Section 3				
	I lazal ugus inuleulents / lu	dentity Information	on	
Sections			on	
	Where present, listed constituent		on	
May Contain the Following			on %	
	Where present, listed constituent	s exist as a solid.		
May Contain the Following	Where present, listed constituent Hazardous Components Glass wool filament	cs exist as a solid.	%	
May Contain the Following Section 4	Where present, listed constituent Hazardous Components Glass wool filament First Aid Measures	cAS No. 65997-17-3	% <100	
May Contain the Following	Where present, listed constituent Hazardous Components Glass wool filament	c exist as a solid. CAS No. 65997-17-3 n artificial respiration a ghing, or breathing is	% <100 and obtain med	
May Contain the Following Section 4	Where present, listed constituent Hazardous Components Glass wool filament First Aid Measures If breathing has stopped, perform If persistent irritation, severe cou	cAS No. CAS No. 65997-17-3 n artificial respiration a ghing, or breathing is sible.	% <100 and obtain med difficult, provide	e fresh air and seek
May Contain the Following Section 4 Inhalation	Where present, listed constituent Hazardous Components Glass wool filament First Aid Measures If breathing has stopped, perform If persistent irritation, severe cou medical attention as soon as poss If the product or dust is swallowed Do not induce vomiting.	cAS No. CAS No. 65997-17-3 n artificial respiration a ghing, or breathing is sible. ed, seek immediate me hould receive immedia ith large amounts of v	% <100 and obtain med difficult, provide edical attention ate medical atte	e fresh air and seek or advice. ntion. Dust may be
May Contain the Following Section 4 Inhalation Ingestion	Where present, listed constituent Hazardous Components Glass wool filament First Aid Measures If breathing has stopped, perform If persistent irritation, severe cour medical attention as soon as poss If the product or dust is swallowed Do not induce vomiting. Eye injuries from solid particles so flushed from eyes immediately w	CAS No. CAS No. 65997-17-3 n artificial respiration a ghing, or breathing is sible. ed, seek immediate me hould receive immedia ith large amounts of v ion. ed promptly with thou detergent and water.	% <100 and obtain med difficult, provide edical attention ate medical attention ate medical attention ough cleansing	e fresh air and seek or advice. ntion. Dust may be lower and upper lids of the affected area.

F

А

UEI

FOILS, INCORPORATED

GROUP

Y[®]

COMPANY

Section 5	Firefighting Measures	
Flammable/Combustible Properties	Carbon dioxide, carbon monoxide, and other hazardous gases and volatiles may be generated.	
Fire/Explosion	Dusts generated by mechanical or abrasive activities may be explosive if mixed in critical proportions with air in the presence of an ignition source. Phenolic burns like wood, although it is dangerous and may burn hotter. Partially burned dust is especially hazardous if dispersed into the air. Remove burned or wet dust to an op area after fire is extinguished.	
Extinguishing Media	Same as for a wood fire (water, carbon dioxide, dry chemical, foam or sand).	
Firefighting Equipment/Instructions	For a dust fire confined to a small area, use a respirator approved for toxic dusts and fumes.	
Section 6	Accidental Release Measures	
Personal Precautions	Product in solid form may be picked up by hand or other means to be placed into a container.	
Environmental Precautions	Should waste disposal be deemed necessary, follow Federal, State, or Local regulations.	
Methods for Cleaning Up	Do not use compressed air for cleaning.	
Section 7	Handling and Storage	
	This product does not require special safety precautions for handling. Operations such as grinding, cutting, sanding and shearing may generate dusts or fumes which may require special handling procedures.	
Section 8	Component Exposure Limits	
Appropriate Engineering Controls	When machining, use adequate local (preferably) or general exhaust ventilation to ensure that concentrations of dusts or fumes do not exceed exposure limits. Keep workplace clean and dry. Train personnel to minimize exposure to hazards during installation and replace- ment of product. On a regular basis, verify condition and proper function of equipment in which the product will be installed.	
Personal Respiratory Protection	Use an approved respirator, with the proper assigned protection factor, whenever airborne concentrations of hazardous components exceed listed exposure limits.	
Personal Hand Protection	Use appropriate gloves for periods of longer exposure or to protect against physical hazards.	
Eye Protection	Always wear safety glasses with side shields and appropriate hearing protection when grinding or cutting.	
Skin Protection	For brief contact with dust, no precautions other than clean clothing are usually required.	
	Hazardous Components CAS No. OSHA (PEL/TWA) ACGIH TLV	
	Glass wool filament65997-17-35 mg/m³ (Respirable Dust)10 mg/m³ (Respirable Dust)	

FOILS, INCORPORATED

GROUP

F

UEI

А

Y®

COMPANY

NIT

Section 9	Physical and Chemical Propert	ies	
Appearance/Odor	Fiberglass board, color may vary/solid	Odor Threshold	No data
рН	No data	Boiling Point	No data
Melting Point	No data	Solubility (H ₂ O)	Insoluble in water
Specific Gravity	1.65–2.20	Density	0.04-0.07 lb/in3 (1.2-1.8g/cc)
Octanol/H ₂ O Coefficient	No data	Evaporation Rate	Not volatile
Molecular Weight	No data Decompos	ition Temperature	No data
Auto Ignition	No data Lower F	lammability Limit	No data
Flash Point	No data Upper F	lammability Limit	No data
Vapor Density	No data	Vapor Pressure	No data
VOC	No data F	lammability Class	No data
Viscosity	No data		
Section 10	Chemical Stability and Reactiv	ity	
Stability	Stable under normal handling conditio	ns	
Incompatibility	Oxidizers, strong acids and bases		
Hazardous Decomposition/			
By-Products	Oxides of carbon and nitrogen, phenol,	and formaldehyde if	heated in excess of 570°F (300°C)
Hazardous Polymerization	Contact of dust with strong oxidizers m		
Section 11	Toxicological Information		
Possible effects			
by routes of exposure			
Inhalation	Dust may cause nasal dryness, irritation, coughing, sneezing and sinusitis due to the me- chanical reaction to the fibers. For most individuals, the irritation generally does not persist and the effect will subside after the worker is removed from the exposure. Repeated exposures (even below 5 mg/m ³) to certain dusts can produce allergic responses in some sensitive individuals.		
Eye Contact	Dust may cause temporary mechanical irritation or a burning sensation to the eyes.		
Skin Contact	Dust may evoke allergic contact dermatitis in sensitized individuals.		
Ingestion	Ingestion of significant amounts of product is unlikely. If swallowed and person is conscious give large quantities of water to drink. Get medical attention as soon as possible. Serious effects may occur if large amounts of dust are swallowed.		
	While no toxicity data is available for t determined for their constituents:	he composite solid	s, the following data has been
Glass wool fiber	LD _{LO} inhalation, 0.1 mg/m ³ . IARC lists gl genicity to humans.)	ass wool in Group 3	(not classifiable as to its carcino-

FOILS, INCORPORATED

GROUP

F

А

UEI

Y[®]

COMPANY

Section 12	Ecological Information
Ecotoxicity	Not biodegradable. This product is not expected to present an environmental hazard. Avoid releasing dusts and fumes into the environment.
Persistence/Degradability	No Data
Bioaccumulative Potential	No Data
Mobility in Soil	No Data
Section 13	Disposal Considerations
Disposal Instructions	Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.
Section 14	Transportation Information
	The material is not regulated under DOT provisions.
Section 15	Regulatory Information
U.S. TSCA Inventory Status	All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
Canada DSL Inventory Status	All ingredients of this product are listed or are excluded from listing on the Domestic Substances List (DSL), the Non-Domestic Substances List (NDSL) or exempt.
CERCLA/SARA Section 302	Not listed
SARA (311, 312) Hazard Class	Not listed
CERCLA/SARA Section 313	Not listed
California Prop 65	This product is not subject to the reporting requirements under California's Proposition 65.
WHMIS Hazard Classification	Not listed

Safety Data **S**heet

9090 Nieman Road • Overland Park, KS 66214 • (913) 888-7340 • Toll Free: 877-932-3645 • info@infinityfoils.com • infinityfoils.com

Section 16	Other Information	

UEI

Infinity Foils, Inc. provides the information contained herein in good faith. It is believed to be correct. However it is not all-inclusive and should be used only as a guide. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Infinity Foils, Inc. shall not be held liable for any damage resulting from handling or from contact with this product. All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources.

COMPANY

Abbreviations PEL Permissible Exposure Limit TLV Threshold Limit Value

End Notes 1. SARA - Signed into law in 1986, the Superfund Amendments and Reauthorization Act (SARA) is an extension of CERCLA, and is intended to encourage and support local and state emergency planning efforts. SARA provides citizens and local governments with information about potential chemical hazards, and calls for facilities that store hazardous materials to provide officials and citizens with data on the type and amount on hand at specific locations. This field states whether a material is listed or not listed in section 372.65 of SARA. EHS - This states if a material is listed or not listed in Appendix B to part 355, the SARA Extremely Hazardous Substances (EHS) section. RQ is the reportable quantity. TPQ is the Threshold Planning Quantity.

FINITY

FOILS, INCORPORATED GROUP

2. RCRA - The Resource Conservation and Recovery Act enacted in 1976 and subsequently amended, controls solidwaste disposal and encourages recycling. This states whether a material is listed or not listed under this regulation. If listed the Hazardous Waste Number and waste characterization assigned by RCRA is also provided. 3. CERCLA - Enacted in 1980 and amended thereafter, the Comprehensive Environmental Response, Compensation, and Liability Act provides for identification and cleanup of hazardous materials released on land, into the air, waterways, and groundwater. It covers areas affected by newly released materials and older leaking or abandoned dump sites. This states whether a material is listed or not listed in CERCLA Table 302.4. If listed the section(s) that it is listed under and the Reportable Quantity (RQ) are also provided. 4. TSCA - The Toxic Substances Control Act controls the exposure to and use of raw industrial chemicals not subject to other laws. This states whether the chemical is listed or not listed under this regulation.

15 April 2020 Revision

Supersedes 13 April 2015