

9090 Nieman Road • Overland Park, KS 66214 • (913) 888-7340 • Toll Free: 877-932-3645 • info@infinityfoils.com • infinityfoils.com

## **Cold Stamping Foil – CHCUV Grade**

**Product Data Sheet** 

<b>Foil Specifications</b>
----------------------------

Polyester Film Thickness: 12μm (0.012mm)

Standard Width: 25" (64cm),

**Standard Length(s):** 5000' (1524m); 10,000' (3048m); 15,000' (4572m); 20,000' (6096m);

Custom Widths and Lengths: on 3" or 6" Cores

Available upon request

**Stamping Effects** 

Use: Special purpose foil for cold foiling

**Applications:** Can be used on a wide range of paper and all

types of label stock

**Press Needs:** Can be used on suitably modified reel-to-reel label printers

and sheet-fed litho machines with a cold-foiling station

**Release:** Very easy

**Detail:** Medium to Fine **Appearance:** Clear Holographic

**Effects:** Good halftone effects

Overprint with Inks and Varnishes: Yes, dependent on image and other hot stamping foil

Yes, dependent on inks, image and substrates used

Abrasion Resistance: Good abrasion and scratch resistance

Adhesion Characteristics: Adheres to specially formulated adhesive which has been

"printed" on the substrate
Use an appropriate adhesive

Adjust adhesive lay-down to suit the substrate

Adhesive needs to be UV cured before or after foil transfer to

the substrate (dry or wet process)

Running Speed: Dry Process 60–90m/min. with 300 watts/inch UV lamp

Wet Process 30–50m/min. with 400–600 watts/inch UV lamp

## **Storage and Shelf Life Requirements**

Two (2) years in dry, climate-controlled conditions

and stored on its end, not on side

**Industries Served** 

Labels, Packaging, Commercial Printing

Product Application

Wine & Beverage labels, Pharma labels, Health & Beauty

labels, Printed Papers and Packaging

<sup>© 2020</sup> Infinity Foils, Inc.