

Hot Stamping Foil – MNV Series

Product Data Sheet

Foil Specifications

Polyester Film Thickness:	12µm (0.012mm)
Standard Width:	25" (64cm)
Standard Length(s):	200' (61m); 400' (122m); 1000' (305m); 2000' (610m); 3000' (914m); 4000' (1219m)
Custom Widths and Lengths:	Available upon request

Stamping Effects

Release:	Very Easy
Detail:	Medium to Very Broad
Appearance:	Metallic
Overstamp with Foil:	Yes, dependent on image and other hot stamping foil
Overprint with Inks and Varnishes:	Yes

Product Performance

Abrasion Resistance:	Good adhesion, abrasion and scratch resistance
Adhesion Characteristics:	Most coated and uncoated graphic arts paper, bookbinding substrate, and ribbons
Running Temperature:	225–275°F / 107°–135°C

Storage and Shelf Life Requirements

Two (2) years in dry, climate-controlled conditions
and stored on its end, not on side

Industries Served

Bookbinding, Packaging, Commercial Printing,
Specialty Advertising, Greeting Card, Ribbons and Bags

Product Application

Excellent for Combination Foil Stamping/Embossing
applications; Dry and Recycled Paper Substrates;
Bookbinding Substrates; and Ribbons